



QuantaMesh T3024-P05

A Powerful Top-of-Rack
Switch for Data Centers
and Cloud Computing

- **Ultra-low Latency**
- **Multi-Chassis Link Aggregation (MLAG)**
- **OSPF, BGP4 with ECMP**
- **Network Automation**
- **Openflow**



United States

QCT LLC., Silicon Valley office
1010 Rincon Circle, San Jose, CA 95131
TOLL-FREE: 1-855-QCT-MUST
TEL: +1-510-270-6111
FAX: +1-510-270-6161
Support: +1-510-270-6216

China

云达科技, 北京办公室
(Quanta Cloud Technology)
北京市朝阳区东大桥路 12 号润诚中心 2 号楼
TEL: +86-10-5920-7600
FAX: +86-10-5981-7958

云达科技, 杭州办公室
(Quanta Cloud Technology)
浙江省杭州市西湖区古墩路
浙商财富中心 4 号楼 303 室
TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社
日本国東京都港区芝大門二丁目五番八号
牧田ビル 3 階
TEL: +81-3-5777-0818
FAX: +81-3-5777-0819

Taiwan

雲達科技 (Quanta Cloud Technology)
桃園市龜山區文化二路 211 號 1 樓
TEL: +886-3-286-0707
FAX: +886-3-327-0001

Germany

Quanta Cloud Technology Germany GmbH
Hamborner Str. 55, 40472 Düsseldorf
TEL: +49-2405-4083-1300

Other regions

Quanta Cloud Technology
No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan City
33377, Taiwan
TEL: +886-3-327-2345
FAX: +886-3-397-4770



Rear view

The QuantaMesh T3024-P05 is a high performance and low latency layer 2/3/4 Ethernet switch with 24 1/10GbE SFP+ and 2 40GbE QSFP+ ports located in a half-rack width and 1U height rack unit size. The 2 40GbE ports provide 80Gbps to aggregate bandwidth up to the core switch. Each 40 Gigabit Ethernet port can be independently configured as 40GbE or 4 x 10GbE for total 32 ports of 10GbE.

Simplicity

The QuantaMesh T3024-P05 can be managed through an industry standard command-line interface (CLI) which reduces training and operating costs. The QuantaMesh T3024-P05 also supports Simple Network Management Protocol (SNMP) both from standard MIB and private MIB for easy configuration, monitoring, and remote management for the network administrator. The Auto-Installation feature implemented in the QuantaMesh T3024-P05 helps centralized management to simplify deployment of a truly plug-and-play experience. With the evolution from IPv4 to IPv6, the QuantaMesh T3024-P05 is a IPv6 integrated management device.

High Availability

The QuantaMesh T3024-P05 is designed for high availability from both hardware and software perspective. The key features include:

- Spanning Tree with Guarding Features
- Up to 64 Groups of LACP with per Group 32 Member Ports
- Multi-chassis Link Aggregation (MLAG)
- Up to 32 paths ECMP routing for load balancing and redundancy
- Virtual Router Redundancy Protocol (VRRP)

High-Performance L2/L3 access deployments

With the compact 1U form factor, high density 24 1/10G SFP+ and 2 40G QSFP+ ports in the front panel, front to back or back to front airflow design, the QuantaMesh T3024-P05 is ideal for top-of-rack deployments in high-performance, highly demanding data centers. The 640 gigabits per second switching capacity and 476Mpps forwarding rate with low power consumption make the QuantaMesh T3024-P05 a powerful solution to aggregate high-performance servers in the data center.

Software Defined Network (SDN)

SDN has emerged as a new approach to support open, vendor- agnostic, and programmable networks. QNOS is equipped with OpenFlow v1.3 features to fulfill the needs of modern data center applications.

About QCT

Quanta Cloud Technology (QCT) is a global data center solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation data center design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined data center solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.

QuantaMesh T3024-P05 Specifications

Physical ports

- **Port configuration:** 24 1/10GbE SFP+ and 2 40GbE QSFP+ ports
- **Management Port:** Out-of-band management port (RJ-45, 10/100/1000Base-T)
- **Console Port:** 1 (RJ-45)
- **USB:** 1 (v 2.0)

Performance

- **Switching capacity:** 640Gbps
- **Maximum forwarding rate:** 476Mpps
- **Latency:** <1us
- **MAC:** 128K

Layer 2 Features

- **Switching Mode:** Store-and-Forward
- **Spanning Tree:**
 - 802.1w
 - 802.1s
 - Auto Edge
- **VLAN :**
 - IEEE 802.1Q Tagged Base
 - Port-Based
 - QinQ (802.1ad)
- **Storm Control:**
 - Broadcast
 - Unknown Multicast
 - DLF (Unknown Unicast)
- **IGMP Snooping:**
 - v1/v2/v3
 - v1/v2 Querier
 - Immediate Leave
- **MLD Snooping v1/v2**
- **Link Aggregation:**
 - 802.3ad with LACP
 - Static Trunk
 - Unicast/Multicast Traffic Balance over Trunking Port
 - LACP Falback
- **Link State Tracking**
- **Port Backup**
- **Loopback Detection**
- **Private VLAN**

QoS Features

- **Scheduling for priority queue:**
 - WRR, Strict, Hybrid
- **COS:** 802.1p, IP TOS precedence, DSCP
- **DiffServ**
- **iSCSI optimization**

Security Features

- **Static and dynamic port security (MAC-based)**
- **802.1x (MD5, MS-CHAPv2):**
 - Port-based
 - MAC-based
 - Auto VLAN assignment
 - Guest VLAN
 - Unauthenticated VLAN
- **Access Control List:** L2/L3/L4
- **IPv6 ACL:** L3/L4
- **RADIUS:** Authentication, Authorization, Accounting
- **TACACS+:** Authentication
- **SSH 1.5/V2.0**
- **User name and password:**
 - Local Authentication
 - Remote Authentication via RADIUS/TACACS+, AAA
- **Management IP filtering:**
 - SNMP
 - Telnet
 - SSH

- **IP Source Guard**
- **Dynamic ARP inspection (DAI)**
- **DHCP snooping:** IPv4, IPv6
- **Control Plane Policing (CoPP)**
- **Service Prohibit Access**
- **Role Base Access Control (RBAC)**

Layer 3 Features

- **IP Multinetting/CIDR**
- **/31 subnets**
- **Proxy ARP**
- **Static route:** IPv4, IPv6
- **OSPFv2/v3**
- **ECMP**
- **BGP4**
- **IGMP v1/v2/v3**
- **PIM-SM/-SM6**
- **MLD v1/v2**
- **RRPv2**
- **Policy-Based Routing (PBR)**
- **BFD**
- **VRF Lite**

Management Features

- **Industrial command-line interface**
- **CLI filtering**
- **CLI scheduler**
- **Telnet/SSH**
- **Software update:**
 - TFTP, FTP, SCP, SFTP
- **Configuration download/upload:**
 - TFTP, FTP, SCP, SFTP
- **Dual Images**
- **SNMP v1/v2c/v3**
- **SNMP inform v2**
- **RMON1 Groups: 1, 2, 3, & 9**
- **BOOTP:** client/relay
- **DHCP client**
- **DHCP relay**
- **EVENT/Error log**
- **DNS client**
- **Remote PING**
- **Traceroute**
- **SNTPv4**
- **LLDP:**
 - 802.1ab
 - 802.MED
 - Potential error detection
- **UDLD**
- **Port mirroring:** SPAN, RSPAN
- **sFlow v5**
- **Email alerting:** SMTP
- **Error-Disable Recovery**
- **Fluentd**

IPv6 Management

- **IPv4/IPv6 Dual Protocol Stack**
- **ICMPv6**
- **ICMPv6 Redirect**
- **IPv6 Neighbor Discovery**
- **Stateless Autoconfiguration**
- **Manual Configuration**
- **DHCPv6 client**
- **SNMP over IPv6**
- **SSH over IPv6**
- **IPv6 Telnet Support**
- **IPv6 DNS Resolver**
- **IPv6 RADIUS Support**
- **IPv6 TACACS+ Support**
- **IPv6 Syslog Support**
- **IPv6 SNTP Support**
- **IPv6 TFTP Support**

High Availability

- **Multi-Chassis Link Aggregation (MLAG)**

Data Center Features

- **Enhanced Transmission Selection (802.1Qaz)**
- **Priority-based Flow Control (802.1Qbb)**
- **DCBX:** DCBX for ETS, DCBX for PFC
- **FCoE Initiation Protocol (FIP) snooping**

Automation

- **Auto Installation**
- **RESTful API**
- **Ansible**

Virtualization Features

- **VxLAN**

SDN

- **OpenFlow v1.3**

Mechanical

- **Dimension (HxWxD):** 40x220x422mm
- **Weight:** 3.2kg/7.04lbs (NET)

Environmental Specifications

- **Operating temperature:** 0~45°C
- **Operating humidity:** 90% maximum relative humidity

Electrical

- **Power requirement:**
 - 100~240VAC, 50/60Hz
- **Power consumption:** 90 watts
 - (L2 64B line rate; 10G-SR optics, 100% fan duty)

Safety

- **UL, cUL, CB, BSMI, CCC**

EMC

- **CE, FCC, VCCI, KCC, BSMI, CCC**

RoHS

- **Reduction of Hazardous Substances (RoHS) 6**

Supported Optics and Cables

- **1000BASE-T:** Cat 5e and Cat 6A (100m/330 ft)
- **DAC cable (SFP+):** 0.5m, 1m, 1.5m, 2m, 2.5m, 3m, and 5m
- **AOC cable (SFP+, 850nm, MMF):** 1m, 3m, 7m, 10m, 20m, and 100m
- **DAC cable (QSFP+):** 1m, 3m, and 5m
- **DAC cable (QSFP+, fan-out):** 1m, 3m, and 5m
- **AOC cable (QSFP+, 850nm, MMF):** 7m, 10m, and 20m
- **10G optic (SFP+, LC, 850nm, MMF):** 10GBASE-SR optic
- **10G optic (SFP+, LC, 1310nm, SMF):** 10GBASE-LR optic
- **40G optic (QSFP+, MPO, 850nm, MMF):** 40GBASE-SR4
- **40G optic (QSFP+, LC, 1310nm, SMF):** 40GBASE-LR4

Order Information

- **T3024-P05 (1P05BZZ0ST0) (F-2-B)**
- **T3024-P05 (1P05BZZ0ST1) (B-2-F)**
- **Rack-Mount-Kit (1HY9ZZZ058P)**

