

# QuantaMesh T3040-LY3

A Powerful  
Top-of-Rack Switch  
for Data Centers and  
Cloud Computing



The QuantaMesh T3040-LY3 is a high performance layer 2/3/4 Ethernet switch with 40 100BASE-TX/1000BASE-T/10GBASE-T and 8 1/10GBASE-X SFP+ ports in a compact rack unit size.

The 40 10GBASE-T ports are backwards compatible with 100/1000M Ethernet networks. The 8 SFP+ ports can aggregate bandwidth up to the core switch. With the energy saving requirements, the QuantaMesh T3040-LY3 is designed with high power efficiency to save OPEX.

## Simplicity

The QuantaMesh T3040-LY3 can be managed through an industry standard command-line interface (CLI) which reduces training and operating costs. The QuantaMesh T3040-LY3 also supports Simple Network Management Protocol (SNMP) both from standard MIB and private MIB for easy configuration, monitoring, and management by the network administrator remotely. The Auto-Installation feature implemented in the QuantaMesh T3040-LY3 helps centralized management to simplify deployment of a truly plug-and-play experience. With the evolution from IPv4 to IPv6, the QuantaMesh T3040-LY3 is a IPv6 integrated management device.

## High Availability

The QuantaMesh T3040-LY3 is designed for high availability from both hardware and software perspective. The key features include:

- 1+1 hot-swappable power supplies
- Out-of-band management supported
- 802.1w, and 802.1s supported
- Up to 8 ports per link aggregation group (LACP) and up to 64 groups
- Up to 32 paths ECMP routing for load balancing and redundancy
- Virtual Router Redundancy Protocol supported
- Multi-chassis Link Aggregation

## High-Performance L2/L3 access deployments

With the compact 1U form factor, high density 40 100BASE-TX/1000BASE-T/10GBASE-T and 8 1/10GBASE-X SFP+ ports in the front panel, front to back or back to front airflow design, the QuantaMesh T3040-LY3 is ideal for top-of-rack deployments in high-performance, highly demanding data centers. The 960 gigabits per second switching capacity and 714Mpps forwarding rate with low power consumption make the QuantaMesh T3040-LY3 a powerful solution to aggregate high-performance servers in the data center.

- 10GBT
- MLAG, OSPF, BGP4, & ECMP
- Network Automation

## About QCT

Quanta Cloud Technology (QCT) is a global data center solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation data center design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined data center solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.

## Found at: [www.QCT.io/wheretobuy](http://www.QCT.io/wheretobuy)

### United States

QCT LLC., Silicon Valley office  
1010 Rincon Circle, San Jose, CA 95131  
TOLL-FREE: 1-855-QCT-MUST  
TEL: +1-510-270-6111  
FAX: +1-510-270-6161  
Support: +1-510-270-6216

### China

云达科技, 北京办公室  
(Quanta Cloud Technology)  
北京市朝阳区东大桥路12号润诚中心2号楼  
TEL: +86-10-5920-7600  
FAX: +86-10-5981-7958

云达科技, 杭州办公室  
(Quanta Cloud Technology)  
浙江省杭州市西湖区古墩路  
浙商财富中心4号楼303室  
TEL: +86-571-2819-8650

### Japan

Quanta Cloud Technology Japan 株式会社  
日本国東京都港区芝大門二丁目五番八号  
牧田ビル3階  
TEL: +81-3-5777-0818  
FAX: +81-3-5777-0819

### Taiwan

雲達科技 (Quanta Cloud Technology)  
桃園市龜山區文化二路211號1樓  
TEL: +886-3-286-0707  
FAX: +886-3-327-0001

### Germany

Quanta Cloud Technology Germany GmbH  
Hamborner Str. 55, 40472 Düsseldorf  
TEL: +49-2405-4083-1300

### Other regions

Quanta Cloud Technology  
No. 211 Wenhua 2nd Rd., Guishan Dist.,  
Taoyuan City 33377, Taiwan  
TEL: +886-3-327-2345  
FAX: +886-3-397-4770

QCT authorized partner



# QuantaMesh T3040-LY3

## Physical ports

- **Port configuration:** 40 100/1000/10GBT and 8 1/10GbE SFP+ ports
- **Management Port:** Out-of-band management port (RJ-45, 10/100/1000Base-T)
- **Console Port:** 1 (RJ-45)
- **USB:** 1 (v 2.0)

## Performance

- **Switching capacity:** 960Gbps
- **Maximum forwarding rate:** 714Mpps
- **Latency:** <3us
- **MAC:** 128K

## L2 Features

- **Switching mode:** store-and-forward
- **Spanning Tree:**
  - 802.1D, 802.1w
  - Auto Edge
- **VLAN :**
  - IEEE 802.1Q tagged base
  - Port-Based
  - QinQ (802.1ad)
- **Storm control:**
  - Broadcast
  - Unknown multicast
  - DLF (Unknown unicast)
- **IGMP snooping:**
  - v1/v2/v3
  - v1/v2 Querier
  - Immediate Leave
- **Link Aggregation:**
  - 802.3ad with LACP
  - Static Trunk
  - Unicast/Multicast Traffic Balance over Trunking Port
  - LACP Fallback
- **Link state**
- **Port backup**
- **Error-Disable Recovery**

## QoS Features

- **Scheduling for priority queue:** WRR, Strict, and Hybrid
- **COS:** 802.1p, IP TOS precedence, & DSCP
- **DiffServ**
- **iSCSI optimization**

## Security Features

- **static and dynamic port security (MAC-based)**
- **802.1x:** Port-based, MAC-based, auto VLAN assignment, guest VLAN, unauthenticated VLAN
- **Access Control List:** L2/L3/L4
- **IPv6 ACL:** L3/L4
- **RADIUS:** Authentication and accounting
- **SSH 1.5/V2.0**

- **User name and password:**
  - Local Authentication, Remote Authentication via RADIUS/TACACS+, AAA
- **Management IP filtering:**
  - SNMP/Telnet/SSH
- **IP Source Guard**
- **Dynamic ARP inspection (DAI)**
- **DHCP snooping:** IPv4, IPv6
- **Control Plane Policing / CoPP**
- **Service Prohibit Access**

## Layer 3 Features

- **IP Multinetting/CIDR**
- **/31 subnets**
- **Proxy ARP**
- **Static route:** IPv4, IPv6
- **OSPF**
- **ECMP**
- **BGP4**
- **IGMP v1/v2/v3**
- **PIM-DM/-SM**
- **RRRP**
- **Policy-based routing**
- **BFD**
- **VRF Lite**

## IPv6 L3 Features

- **OSPFv3**
- **MLD v1/v2**
- **PIM-DM6/-SM6**

## Data Center Features

- **Enhanced Transmission Selection (802.1Qaz)**
- **Priority-based Flow Control (802.1Qbb)**
- **DCBX:** DCBX for ETS, DCBX for PFC
- **FCoE Initiation Protocol (FIP) snooping**

## SDN

- **OpEN API:** RESTful API
- **OpenFlow:** v1.3

## Management Features

- **Industrial standard command-line interface**
- **CLI filtering**
- **CLI schedule**
- **Telnet/SSH**
- **Software download/upload:**
  - TFTP, FTP, SCP, SFTP
- **Configuration download/upload:**
  - TFTP, FTP, SCP, SFTP
- **Dual Image**
- **SNMP v1/v2c/v3:** Yes (read only)
- **SNMP inform:** v2/v3
- **RMON 1, 2, 3, & 9:** Yes (read only)
- **BOOTP:** client/relay
- **DHCP client**
- **DHCP relay**
- **DNS client**
- **DNS relay**
- **Remote PING**
- **Traceroute**
- **SNTPv4**
- **LLDP:**
  - 802.1ab
  - 802.MED
  - Potential error detection
- **UDLD**

## Port mirroring:

- **SPAN, RSPAN**
- **sFlow v5**
- **Email alerting**
- **Auto Install**

## IPv6 Management

- **IPv4/IPv6 Dual Protocol Stack**
- **ICMPv6**
- **ICMPv6 Redirect**
- **IPv6 Neighbor Discovery**

- **Stateless Autoconfiguration**
- **Manual Configuration**
- **DHCPv6:** Yes (client)
- **SNMP over IPv6**
- **SSH over IPv6**
- **IPv6 Telnet Support**
- **IPv6 DNS Resolver**
- **IPv6 RADIUS Support**
- **IPv6 TACACS+ Support**
- **IPv6 Syslog Support**
- **IPv6 SNMP Support**
- **IPv6 TFTP Support**

## High Availability

- **Redundant power supply:** 1+1
- **Multi-chassis LAG**

## Mechanical

- **Dimension (HxWxD):** 42.8x435x393mm
- **Weight:** 7.9kg/17.42lbs (NET)

## Environmental Specifications

- **Operating temperature:** 0~45°C
- **Operating humidity:** 90% maximum relative humidity

## Electrical

- **Power requirement:**
  - 100~240VAC, 50/60Hz
- **Power consumption:** 376 watts
  - (L2 64B line rate; Cat 6A, 100% fan duty)

## Safety

- **UL, cUL, CB, BSMI, CCC**

## EMC

- **CE, FCC, VCCI, BSMI, CCC**

## RoHS

- **Reduction of Hazardous Substances (RoHS) 6**

## Supported Optics and Cables

- **1000BASE-T:** Cat 5e and Cat 6A (100m/330 ft)
- **10GBAE-T:** Cat 6A (100m/330ft)
- **DAC cable (QSFP+):** 1m, 3m, and 5m
- **DAC cable (QSFP+, fan-out):** 1m, 3m, and 5m

## Order Information

- **T3040-LY3 (1LY3BZZ0ST8) (F-2-B, AC, P2020)**
- **T3040-LY3 (1LY3BZZ0ST9) (B-2-F, AC, P2020)**
- **PSU - Blue (1HY9ZZZ015H) (F-2-B, AC, 750W)**
- **PSU - Green (1HY9ZZZ015I) (B-2-F, AC, 750W)**

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their respective holders. Copyright © 2014-2017 Quanta Computer Inc. All rights reserved.

