QuantaMesh **BMS T3096-LY5**





A Powerful Spine/Leaf Switch for Datacenter and **Cloud Computing**

ONIE Pre-loaded

- SDN Ready
- High Availability
- Ultra-low Latency

Datacenter networks are facing a major paradigm shift toward the disaggregation of software and hardware. This move, combined with the benefits of software-defined networking (SDN) allows network administrators respond quickly to changing business requirements at a lower capital cost as well as reducing the network operations complexity.

QuantaMesh BMS products offer higher performance, increased availability, low latency and better serviceability. QuantaMesh T3096-LY5 supports 96 SFP+ (1/10GbE speed) ports in a compact 1U size. By leveraging the new generation merchant silicon chips, T3096-LY5 is a high performance high density Ethernet switch with an affordable price for the deployment of data center infrastructure. With ONIE (Open Network Installation Environment) pre-loaded on QuantaMesh BMS switches, it provides the flexibility and allows choice of network operating system supported by ONIE installer. This provides agile installation process and faster response for the changing business demand.

About QCT

QCT (Quanta Cloud Technology) is a global datacenter solution provider extending the power of hyperscale datacenter design in standard and open SKUs to all datacenter customers. Product lines include servers, storage, network switches, integrated rack systems and cloud solutions, all delivering hyperscale efficiency, scalability, reliability, manageability, serviceability and optimized performance for each workload. QCT offers a full spectrum of datacenter products and services from engineering, integration and optimization to global supply chain support, all under one roof. The parent of QCT is Quanta Computer Inc., a Fortune Global 500 technology engineering and manufacturing company.

Physical ports

- · Port configuration: 96 1/10GbE SFP+ ports
- · Management Port: Out-of-band management port (RJ-45, 10/100/1000Base-T)
- · Console Port: 1 (RJ-45)
- · USB: 1 (v 2.0)

Performance

- MAC: Unified Forwarding Table to dynamically allocate the L2/L3 tables

- · Hot-swappable fan tray: N+1
- Mechanical

Electrical

- · Power requirement: 100~240VAC, 50/60Hz
- · Power consumption: 376 watts (L2 64B line rate; 10G-SR optics,
- 100% fan duty)
- · Safety: UL, cUL, CB · EMC: CE, FCC
- RoHS
- · Reduction of Hazardous Substances
- (RoHS) 6

Get a quote: www.QuantaQCT.com

United States

QCT LLC., Silicon Valley office 1010 Rincon Circle, San Jose, CA 95131 TOLL-FREE: 1-855-QCT-MUST TEL: +1-510-270-6111 FAX: +1-510-270-6161 Support: +1-510-270-6216

China

云达科技,北京办公室(Quanta Cloud Technology) Room 1508, East Tower 15F, World Financial Center, No.1, East 3rd Ring Zhong Rd., Chaoyang District, Beijing, China TEL: +86-10-5920-7600 FAX: +86-10-5981-7958

云达科技,杭州办公室(Quanta Cloud Technology) Room 303, Building No.4, ZheShang Wealth Center, No.83, GuDun Rd., Xihu District, Hangzhou, Zhejiang, China TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社 Makita Building 3F, 2-5-8, Shibadaimon , Minato-ku, Tokyo 105-0012, Japan TEL: +81-3-5777-0818 FAX: +81-3-5777-0819

Taiwan

雲達科技(Quanta Cloud Technology) TF, No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan TEL: +886-3-286-0707 FAX: +886-3-327-0001

Other regions

Quanta Cloud Technology No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan TEL: +886-3-327-2345 FAX: +886-3-397-4770

QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their representative holders. Copyright © 2014-2015 Quanta Computer Inc. All rights reserved.

· Switching capacity: 1920Gbps · Maximum forwarding rate: 1428Mpps • Latency: <600ns

High Availability

· Redundant power supply: 1+1

· Dimension (HxWxD): 87x435x410mm

· Weight: 11.4kg/25lbs (NET)

- **Environmental Specifications**
- · Operating temperature: 0~45°C
- · Operating humidity:
- 90% maximum relative humidity