

QuantaGrid D51BP-1U

Energy Efficient 2-Socket
Server with Extreme
Storage IOP/S



QuantaGrid D51BP-1U is a revolutionary 1U rackmount server that dramatically increases data storage IOPS. All ten 2.5" front access drive bays support hot-pluggable PCIe I/O interface. Owners can tailor system storage architecture by mixing traditional hard disk drives and Non-Volatile Memory Express (NVMe) SSD.

Greener and More Powerful

Powered by Intel® Xeon® processor E5-2600 v3 product family and the DDR4 memory technology, it allows owners to upgrade computing performance without compromising power consumption. Also with QCT's enhanced thermal and power design, the server can operate under 35°C ambient temperature without throttling even if a fan rotor fails. This allows you to save unnecessary datacenter cooling cost and achieve higher DCIE (Data center infrastructure efficiency) value.

Ultra Low Latency NVMe Solution

NVMe is an innovative host controller interface specification for SSDs to be accessed through the PCIe bus. The data bandwidth increases to five times the traditional SATAIII interface (6Gb/s compared with 31.5Gb/s of PCIe3.0x4), and the new interface significantly reduces the latency caused by register access. This solution efficiently supports multi-core architectures and SR-IOV for data-intensive virtualization workloads. On QuantaGrid D51BP-1U, all ten 2.5" front access drive bays support hot-pluggable PCIe I/O interface. Owners can combine traditional hard disk drives and NVMe-based SSDs to tailor system storage architecture to their needs.

- Ultra Low Latency NVMe Solution
- Greener and More Powerful
- Flexible and Scalable I/O options



Flexible and Scalable I/O options

QuantaGrid D51BP-1U provides flexible I/O scalability for today's diverse data center application requirements. It features OCP LAN mezzanine card solutions in addition to dual GbE or 10GbE LAN on motherboards (LoM). With various controller vendors and different speed and technology options, customers can choose from 1GbE to 56GbE bandwidth, copper or fiber-optic cabling, basic Ethernet function or FCoE and ISCSI SAN connectivity. The onboard SAS controller offers multiple QCT SAS mezzanine card options with different RAID levels and data transfer bandwidth so customers can tailor the SAS controller for specific application needs.

About QCT

QCT (Quanta Cloud Technology) is a global datacenter solution provider extending the power of hyperscale datacenter design in standard and open SKUs to all datacenter customers.

Product lines include servers, storage, network switches, integrated rack systems and cloud solutions, all delivering hyperscale efficiency, scalability, reliability, manageability, serviceability and optimized performance for each workload.

QCT offers a full spectrum of datacenter products and services from engineering, integration and optimization to global supply chain support, all under one roof.

The parent of QCT is Quanta Computer Inc., a Fortune Global 500 technology engineering and manufacturing company.

<http://www.QuantaQCT.com>

QuantaGrid D51BP-1U



Get a quote: www.QuantaQCT.com

United States

QCT LLC., Silicon Valley office
1010 Rincon Circle, San Jose, CA 95131
TOLL-FREE: 1-855-QCT-MUST
TEL: +1-510-270-6111
FAX: +1-510-270-6161
Support: +1-510-270-6216

China

云达科技 北京办公室 (Quanta Cloud Technology)
Room 1508, East Tower 15F, World Financial
Center, No.1, East 3rd Ring Zhong Rd., Chaoyang
District, Beijing, China
TEL: +86-10-5920-7600
FAX: +86-10-5981-7958

云达科技 杭州办公室 (Quanta Cloud Technology)
Room 303, Building No.4, ZheShang Wealth Center,
No.83, GuDun Rd., Xihu District, Hangzhou,
Zhejiang, China
TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社
Makita Building 3F, 2-5-8, Shibadaiimon, Minato-ku,
Tokyo 105-0012, Japan
TEL: +81-3-5777-0818
FAX: +81-3-5777-0819

Taiwan

雲達科技 (Quanta Cloud Technology)
1F, No. 211 Wenhua 2nd Rd., Guishan Dist.,
Taoyuan City 33377, Taiwan
TEL: +886-3-286-0707
FAX: +886-3-327-0001

Other regions

Quanta Cloud Technology
No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan
City 33377, Taiwan
TEL: +886-3-327-2345
FAX: +886-3-397-4770

QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their representative holders.
Copyright © 2014-2015 Quanta Computer Inc. All rights reserved.

Processor	Processor Type: Intel® Xeon® processor E5-2600 v3 product family Max. TDP Support: 135W (145W with limited conditions) Number of Processors: 2 Internal Interconnect: 6.4 / 8.0/ 9.6 GT/s L3 Cache: Up to 45MB
Chipset	Intel® C610
Memory	Total Slots: 20 Capacity: Up to 640GB RDIMM Up to 1280GB LRDIMM Memory Type: 2133 MHz DDR4 RDIMM/ LRDIMM Memory Size: 32GB, 16GB, 8GB RDIMM 64GB, 32GB LRDIMM
Network Controller	LOM: Option 1: Intel® I350 dual-port 1 GbE Dedicated 1 GbE management port Option 2: Intel® X540 dual-port 10GbE BASE-T Dedicated 1 GbE management port Optional NIC (more options refer to the CCL): Please refer to our Compatible Component List for more information
Storage Controller	Onboard: (2) SATADOM Optional Controller (more options refer to the CCL): Please refer to our Compatible Component List for more information
Onboard Storage	(2) SATADOM
Video	Integrated AST2400 with 8MB DDR3 video memory
Rear I/O	(2) USB 3.0 ports (1) VGA port (1) RS232 serial Port (2) 1 GbE or 4x 1G RJ45 port (1) GbE RJ45 management port (1) ID LED (1) System status LED
TPM	Yes (With TPM 1.2/ 2.0 option)
Form Factor	1U Rack Mount
Dimensions	W x H x D (inch): 17.244 x 1.7 x 29.21 W x H x D (mm): 438 x 43.2 x 742
Storage	10x 2.5" hot-plug (support PCIe-based interface)
Expansion Slot	Option 1 (default): (1) PCIe Gen3 x8 SAS mezzanine slot, (2) PCIe Gen3 x8 LP MD-2, (1) PCIe Gen3 x8 OCP LAN mezzanine slot Option 2: (this sku does not support any 2.5" PCIe SSD) (1) PCIe Gen3 x8 SAS mezzanine slot, (1) PCIe Gen3 x8 OCP LAN mezzanine slot, (2) PCIe Gen3 x16 LP MD-2
Front I/O	None
Power Supply	1+1 High efficiency redundant hot-plug PSU (default with one PSU only; detailed PSU options please refer to "ordering info" or "Compatible Component List")
Fan	(6) dual rotor fans (11+1 redundant)
System Management	IPMI v2.0 Compliant, on board "KVM over IP" support Quanta Datacenter Manager 2.0/QDCM 2.0 (Optional)
Operating Environment	Operating temperature: 5°C to 35°C (41°F to 95°F) Non-operating temperature: -40°C to 65°C (-40°F to 149°F) Operating relative humidity: 50% to 85%RH Non-operating relative humidity: 20% to 90%RH
Weight (Max. Configuration)	20.81 (kg)

Build a more secure Cloud with Intel® Technology.

Intel, the Intel logo, Xeon, the Xeon inside, Intel Atom and Intel Atom Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries.

