

QuantaMesh BMS T7080-IXA



Networking Router for Carrier Networks and Service Providers

- 80 x 100G QSFP28
- ArcOS® Ready
- BMC supported

QCT QuantaMesh T7080-IXA is an open core router platform that supports 80 100GbE ports in a compact 2U form factor. In a total bandwidth of 8 Terabits per second, IXA offers a high-density solution for core-layer deployments in the central office. Equipped with two Broadcom Jericho 2 BCM88690 chips, the QCT QuantaMesh T7080-IXA is rated at 4B PPS processing and includes a 16GB deep packet buffer with HBM. With deep buffer and large table size, IXA enables lossless forwarding with high-density. The telemetry features enable IXA to operate network traffic more efficiently in the core-layer of networks.

High Availability

The QuantaMesh BMS IXA is purpose-built for carrier network. The key features from both hardware and software perspectives include:

- 4B PPS packet processing
- Hierarchical Traffic Management with Deep Buffer
- 128K queues
- 16GB deep packet buffer using HBM
- Real-time telemetry and analysis
- BMC supported
- Compact 2RU form factor
- Redundant PSUs and Fans

About QCT

Quanta Cloud Technology (QCT) is a global data center solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation data center design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined data center solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.





Found at: www.QCT.io/wheretobuy

United States

QCT LLC, Silicon Valley office
1010 Rincon Circle, San Jose, CA 95131
TOLL-FREE: 1-855-QCT-MUST
TEL: +1-510-270-6111
FAX: +1-510-270-6161
Support: +1-510-270-6216

China

云达科技, 北京办公室
(Quanta Cloud Technology)
北京市朝阳区东大桥路12号润诚中心2号楼
TEL: +86-10-5920-7600
FAX: +86-10-5981-7958

云达科技, 杭州办公室

(Quanta Cloud Technology)
浙江省杭州市西湖区古墩路浙商财富中心4号楼
303室
TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社
日本国東京都港区芝大門二丁目五番八号
牧田ビル3階
TEL: +81-3-5777-0818
FAX: +81-3-5777-0819

Taiwan

雲達科技 (Quanta Cloud Technology)
桃園市龜山區文化二路211號1樓
TEL: +886-3-286-0707
FAX: +886-3-327-0001

Germany

Quanta Cloud Technology Germany GmbH
Hamborner Str. 55, 40472 Düsseldorf
TEL: +49-211-74077-300

Other regions

Quanta Cloud Technology
No. 211 Wenhua 2nd Rd., Guishan Dist.,
Taoyuan City 33377, Taiwan
TEL: +886-3-327-2345
FAX: +886-3-397-4770

QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their respective holders.
Copyright © 2020 Quanta Computer Inc. All rights reserved.

Physical Ports

- **Port configuration:** 80 100G QSFP28 ports
- **Management Port:** 1 RJ-45 out-of-band management port (10/100/1000M)
- **Console Port:** 1 (RJ-45)
- **USB:** USB 2.0

Performance

- **Switching capacity:** 16Tbps
- **Maximum forwarding rate:** 4B PPS
- **MAC:** Unified Forwarding Table to dynamically allocate the L2/L3 tables

Major Components

- **ASIC:** Broadcom Jericho2 BCM88690 *2
- **Packet buffer:** 16GB
- **CPU:** Intel Broadwell DE D-1548
- **Memory:** 16GB*2 SO-DIMM DDR4
- **Flash:** 16MB*2
- **Storage:** 128G SSD M.2

Mechanical

- **Dimension (HxWxD):** 86.5x440x620 mm
- **Weight:** 26.49KG(NET)

Environmental Specifications

- **Operating temperature:** 0°C to 45°C @sea level (F-B)
- **Operating humidity:** 90% maximum relative humidity
- **Operating Altitude:** 0 to 2952 ft, (0-900m)

Electrical

- **Power requirement:** 100~240V AC, 50/60Hz
-40~-56V DC
- **Power consumption:** 1600W*4

Safety

- **UL, cUL, CB**

EMC

- **CE, FCC**

RoHS

- **Reduction of Hazardous Substances (RoHS) 6**

Supported Optics and Cables

- **Cables:**
 - 40G Direct Attach Copper Cable (QSFP+ to QSFP+): 1m, 3m, and 5m
 - 100G Direct Attach Copper Cable (QSFP28 to QSFP28): 0.5m~5m
 - 40G Active Optical Cable (QSFP+, 850nm, MMF): 7m and 10m
 - 100G Active Optical Cable (QSFP28, 850nm, MMF): 1m, 3m, 5m, and 10m
- **Break-out Cables:**
 - 40G Direct Attach Copper Cable (QSFP+ to 4 SFP+): 1m, 3m, and 5m
 - 100G Direct Attach Copper Cable (QSFP28 to 4 SFP28): 3m
- **Optics:**
 - 40G optic (QSFP+, MPO, 850nm, MMF): 40GBASE-SR4
 - 40G optic (QSFP+, LC, 1310nm, SMF): 40GBASE-LR4
 - 100G Optic (QSFP28, MPO, 850nm, MMF): 100GBASE-SR4
 - 100G Optic (QSFP28, LC, 1310nm, SMF): 100GBASE-LR4
 - 100G Optic (QSFP28, LC, 1310nm, SMF): 100GBASE-DR1
 - 100G Optic (QSFP28, LC, 1310nm, SMF): 100GBASE-FR1
 - 100G Optic (QSFP28, LC, 1271~1331nm, SMF): 100GBASE-CWDM4



Powered by Intel®
Xeon® processors

Intel, the Intel logo, Intel Inside, Intel Inside logo, Intel Atom and Intel Atom Inside are trademarks of Intel Corporation in the U.S. and/or other countries.